



## Illuminator Accessories

MODEL	SMB1	DMB1	TMB1	PMB1
<b>Description</b>	'L' wall mount bracket for single illuminator	Dual illuminator mounting bracket	Triple Illuminator mounting bracket	Single Pole mounting bracket
<b>Compatibility</b>	Compatible with all Clarius Infra-Red & White light illuminators	Compatible with all Clarius Infra-Red & White light illuminators	Compatible with all Clarius Infra-Red & White light illuminators	Compatible with all Clarius Infra-Red & White light illuminators
<b>Adjustable</b>	Fully adjustable (left, right, up & down) Allows up to 180 degrees rotation	Fully adjustable (left, right, up & down) Doubles the angle of illumination Increases illumination distance by a factor of 1.4x when using two equivalent illuminators Mix-and-match illuminators (angle & distance) Mix-and-match Infra-Red & White-Light illuminators for Hybrid models	Fully adjustable (left, right, up & down) Triples the angle of illumination Increases illumination distance by a factor of 1.7x when using three equivalent illuminators Mix-and-match illuminators (angle & distance) Mix-and-match Infra-Red & White-Light illuminators for Hybrid models	Supplied with stainless steel straps to fit 7.5 to 20 cm diameter pole
<b>Housing</b>	Stainless steel construction (black powder coated)	Stainless steel construction (black powder coated)	Stainless steel construction (black powder coated)	Stainless steel construction
<b>IP Rating</b>		Includes IP67 rated junction box	Includes IP67 rated junction box	
<b>Weight</b>	200g	550g	750g	700g

MODEL	ALT-30-24	ALT-60-24	ALT-100-24	ALT-150-24
<b>Power:</b>	30W	60W	100W	150W
<b>Output:</b>	24V DC / 1.25A	24V DC / 2.5A	24V DC / 4.2A	24V DC / 6.25A
<b>Input:</b>	170-250V AC / 0.45A 50/60 Hz	170-250V AC / 0.85 A 50/60 Hz	170-250V AC / 1.25 A 50/60 Hz	170-250V AC / 1.25 A 50/60 Hz
<b>Rating:</b>	IP67	IP67	IP67	IP67
<b>Dimensions</b>	200 x 20 x 29mm L x W x H	150 x 44 x 63mm L x W x H	214 x 44 x 63mm L x W x H	214 x 44 x 63mm L x W x H