

ActiV Conventional Weatherproof Hi-Output 100dB(A) Wall Sounder (IP55)

Part No. **BF430C/CC/DR/65**

**C-TEC
Manufactured**



Overview

- Third-party certified to EN54-3 (Sounders).
- Impressive 100dB(A) sound output @ 1m.
- Includes 31 selectable primary tones and an optional secondary tone.
- Two volume levels (high and low)
- Alarm Current at 30Vdc = 5.5mA.
- Alarm Current at 18Vdc = 3.8mA.
- IP55C rated (weatherproof).
- Manufactured in the UK by C-TEC.



Technical Specifications

| | |
|------------------------------------|---|
| Approvals/certifications | Certified to EN54-3 by the LPCB. |
| Protocol/compatibility | Compatible with C-TEC's CFP, FP, MFP and EP203 conventional fire alarm panels and virtually all other makes (testing on third-party panels is recommended before use) |
| Application/operation | Designed to be wall mounted. Weatherproof to IP55C. |
| VAD category & coverage | N/A. |
| Flash rate & colour | N/A. |
| Supply/operating voltage | 18 to 30V DC. |
| Nominal SPL (Sound Pressure Level) | 100dB(A). |



| | |
|----------------------------------|---|
| Alarm current | At 30Vdc: 5.5mA; At 18Vdc: 3.8mA. |
| Product dimensions (mm) | 114mm diameter x 132mm deep. |
| IP Rating | IP55C (Weatherproof). |
| Weight | 315g. |
| Operating conditions/temperature | -10°C to +55°C. Max. 95% RH (Non-condensing). |

