

Hi-Output 103dB(A) Wall Sounder (deep base)

Part No. **BF430A/CX/DR**



Overview

- Third-party certified to EN54-3 (Sounders) and 17 (Isolators) by the LPCB.
- Impressive 103dB(A) sound output @ 1m.
- Onboard short-circuit loop isolator.
- 550µA quiescent current.
- 5mA alarm current @24V DC (sounder on max).
- Group addressing facility allows multiple devices to be operated simultaneously.
- 7 selectable volume levels and up to 15 selectable tone pairs.
- IP33C (Type A) rated.



Technical Specifications

Approvals/certifications

Certified to EN54-3 & 17 by the LPCB

Protocol/compatibility

Compatible with C-TEC's XFP/ZFP XP95/Discovery Addressable Fire Panels.

Application/operation

Designed to be wall mounted. IP33C rated and suitable for use outdoors (note an IP65 rated Sounder VAD version is also available).

VAD category & coverage

N/A.

Flash rate & colour

N/A.

Supply/operating voltage

17 to 28V DC.

Quiescent current

550µA @ 24 VDC.



Nominal SPL (Sound Pressure Level) 103dB(A) when set to tone 1.

Alarm current 5mA (Sounder on max).

Indicators Polling (green LED) & Short Circuit Isolator Active (amber LED).

Product dimensions (mm) 114mm diameter x 131mm deep.

IP Rating IP33C (Type A).

Weight 300g.

Operating conditions/temperature -10°C to +55°C. Max. 95% RH (Non-condensing).

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD, UK

Telephone: 01942 322744

Email: sales@c-tec.co.uk
c-tec.com

You're Safe with C-TEC

