

DS-C30S-02HI/4K 4K HDMI 2-ch Input Board




The video wall controller is mainly used for screen splicing control system, and is the core control device of the system. As a new-generation FPGA-based pure hardware image processing device, it adopts the dual data switching technology and the structure of main control board and service boards. It supports processing and transmitting large data, processing multiple high-definition and ultra-high-definition signals in real time, and managing multiple screens.

- Supports 2 channels of 4K HDMI signal input.
- Supports composite audio input.
- Supports custom resolution.

▪ Specification

Chassis	
Occupied Slot	Input slot
Audio Input	
Audio Input Interfaces	2
Audio Input Interface Type	HDMI composite audio
Audio Sampling Rate	48K sampling rate
Audio Channel	Dual channel
Video Input	
Video Input Interface Type	HDMI 2.0
Video Input Interfaces	2
Max. Video Input Resolution	4K
Video Input Resolution	<p>1920 × 1080P@60 Hz, 1920 × 1200@60 Hz, 3840 × 2160@30 Hz, 3840 × 2160@60 Hz, 4096 × 2160@30 Hz, 4096 × 2160@60 Hz</p> <p>Custom resolution: width ranges from 800 to 8192, height ranges from 600 to 8192. Width must be a multiple of 4 and height must be a multiple of 2. Frame rate is 30 Hz or 60 Hz. When configuring 30 Hz frame rate, the resolution ranges from 1920 × 1080 to 4096 × 2160. When configuring 60 Hz frame rate, the resolution ranges from 800 × 600 to 4096 × 2160.</p>

▪ Dimension



▪ Accessory

▪ Optional



See Far, Go Further



www.hikvision.com
support@hikvision.com

