

# RG-EW7200BE PRO

## BE7200 Wi-Fi 7 Gaming Router



### Highlights

- Unmatched Speed with Wi-Fi 7
- 2 x 2.5 Gbps WAN ports
- 3 x 2.5 Gbps and 4 x 1 Gbps LAN ports
- 9 antennas and 9 FEMs
- Enterprise-grade flagship chip
- Advanced gaming features

## Highlight Features

# Make Barriers None Make Distance Zero

Introducing the RG-EW7200BE PRO, a cutting-edge **WIFI 7** router offering speeds up to 7200 Mbps. Featuring MLO and MRU for superior performance, it delivers exceptional coverage and stability. Experience unparalleled networking performance with the RG-EW7200BE PRO.

## Make Barriers None, Make Distance Zero

With **9 antennas** and **9 FEMs**, the RG-EW7200BE PRO penetrates three walls and eliminates coverage holes, ensuring strong and reliable coverage that makes barriers disappear and distances negligible.



# Highlight Features

## BE7200

With speeds up to 7200 Mbps, the RG-EW7200BE PRO delivers seamless gaming and smooth HD streaming for an exceptional online experience.

up to  
**7.2 Gbps**

## Outstanding Signal Penetration

9 antennas and 9 FEMs ensure strong signal penetration.



## 5 x 2.5 Gbps & 4 x 1 Gbps

Unleash the power of Gigabit Internet.



## Multi-Link Operation

Advanced MLO technology allows devices to simultaneously use multiple bands for faster and more stable wireless data transmission.



## Advanced Gaming Features

Exclusive 2.5 Gbps gaming ports and gaming Wi-Fi ensure a smooth gaming experience.



## Recommended Users: 96

Easily connect all your smart home devices.



## Highlight Features

Build an Ideal Network with  
**5 x 2.5 Gbps & 4 x 1 Gbps Ports**

### Dual-WAN Aggregation

Dual-WAN aggregation combines multiple internet connections to deliver wired bandwidth exceeding 4.2 Gbps.

Load Balancing

Dual-Line Backup

Dual-LAN Aggregation




### USB 3.0 Port

The USB 3.0 port on the RG-EW7200BE PRO supports fast file sharing through external storage devices, allowing multiple devices on the network to access and download files easily—perfect for home and office environments.



# Highlight Features



# Hardware Specifications

Model	RG-EW7200BE PRO
<b>Wi-Fi Radio</b>	
Operating band	IEEE 802.11b/g/n/ac/ax/be, 2.400GHz~2.4835GHz; IEEE 802.11a/n/ac/ax/be, 5.150GHz~5.350GHz; IEEE 802.11a/n/ac/ax/be, 5.470GHz~5.725GHz; IEEE 802.11a/n/ac/ax/be, 5.725GHz~5.850GHz
FEM	2.4GHz: iPA 5GHz: EPA
Max. Wi-Fi Speed	2.4 GHz, 1377 Mbps 5 GHz, 5765 Mbps 2.4 GHz: 802.11b: 22 dBm 802.11g: 6 Mbps 22 dBm; 54 Mbps 20 dBm 802.11n: MCS0 22 dBm; MCS7 19 dBm 802.11ac: MCS0 22 dBm; MCS9 18 dBm 802.11ax: MCS0 22 dBm; MCS11 16.5 dBm 802.11be: MCS0 25 dBm; MCS13 15.5 dBm
Maximum transmit power	5 GHz: 802.11a: 6 Mbps 26 dBm; 54 Mbps 22 dBm 802.11n: MCS0 26 dBm; MCS7 21.5 dBm 802.11ac: MCS0 26 dBm; MCS9 21 dBm 802.11ax: MCS0 26 dBm; MCS11 19 dBm 802.11ax: MCS0 26 dBm; MCS13 17 dBm  Note: The transmit power varies according to regulations in different countries and regions.
MIMO	2.4 GHz, 4 x 4 5 GHz, 4 x 4
Wi-Fi standard	Wi-Fi 7 (IEEE 802.11be)
<b>Antenna</b>	
Antenna	9 x external antennas
Antenna gain (2.4 GHz)	4 dBi
Antenna gain (5 GHz)	5 dBi
<b>Certification and Regulatory Compliance</b>	
Certification	CE, CB
<b>Dimensions and Weight</b>	
Product dimensions (W x D x H)	259 mm x 248 mm x 153 mm (10.2 in. x 9.76 in. x 6.02 in.)

# Hardware Specifications

Model	RG-EW7200BE PRO
Weight	0.739 kg (1.63 lbs) (without packaging materials) 1.44 kg (3.17 lbs) (with packaging materials)
<strong>Environment and Reliability</strong>	
Operating humidity	5% RH to 95% RH (non-condensing)
Operating temperature	0 °C to +40 °C (32 °F to 104 °F)
Storage humidity	5% RH to 95% RH (non-condensing)
Storage temperature	-40 °C to +70 °C (-40 °F to 158 °F)
<strong>Port Specifications</strong>	
LEDs	5 x atmosphere LEDs 1 x system status LED
LAN ports	4 x 10/100/1000/2500BASE-T ports 4 x 10/100/1000BASE-T ports
Number of LAN/WAN ports	1 x 10/100/1000/2500BASE-T port
WAN ports	1 x 10/100/1000/2500BASE-T port
<strong>Power Supply and Consumption</strong>	
Power supply	DC 12 V 3 A
<strong>Product Information</strong>	
Warranty	3 years
<strong>System Specifications</strong>	
RAM	1GB

# Software Specifications

Model	RG-EW7200BE PRO
<b>Basic Configurations</b>	
<b>LED management</b>	Yes
<b>Internet access mode</b>	PPPoE, DHCP, Static IP, WISP, L2TP
<b>Preconfiguration</b>	Yes
<b>Reset and keep configurations</b>	Yes
<b>Restoring factory defaults</b>	Yes
<b>Configuration backup</b>	Yes
<b>Local upgrade</b>	Yes
<b>Online upgrade</b>	Yes
<b>Scheduled upgrade</b>	No
<b>AP mode</b>	Yes
<b>Ethernet Switching</b>	
<b>WAN port aggregation</b>	Yes
<b>LAN port aggregation</b>	Yes
<b>Specifying the VLAN tag</b>	Yes
<b>IP Service</b>	
<b>Port mapping</b>	Yes
<b>ARP binding</b>	Yes
<b>Number of ARP binding entries</b>	64
<b>DDNS</b>	Yes
<b>No-IP DNS</b>	Yes
<b>Ruijie DDNS</b>	Yes
<b>NAT-DMZ</b>	Yes
<b>Number of port mapping entries</b>	50

# Software Specifications

Model	RG-EW7200BE PRO
UPnP	Yes
<b>Behavior Management</b>	
Parental control	Yes
Client access control (based on MAC addresses)	Yes
Client access control (based on time)	Yes
Maximum number of controlled clients	32
Maximum number of parental control policies	32
Selecting clients from the client list to block their access to the Internet	Yes
Specifying MAC addresses of controlled clients	Yes
<b>Ethernet Interface</b>	
MAC address cloning	Yes
VLAN-based IPTV	Yes
<b>Flow Control</b>	
Flow control based on number of users	Yes
Standalone/Shared mode	Yes
Interface flow control	Yes
<b>IPTV/VLAN</b>	
Multiple IPTV ports	Yes
<b>Multicast</b>	
IGMP proxy	Yes
IGMP snooping	Yes
Note: Not supported by wired connections when IPTV is turned on	
<b>Network Management and Monitoring</b>	

# Software Specifications

Model	RG-EW7200BE PRO
<b>Line detection</b>	Yes
<b>Arabic</b>	Yes
<b>Chinese (Hong Kong Traditional)</b>	Yes
<b>Chinese (Simplified)</b>	Yes
<b>English</b>	Yes
<b>Indonesian</b>	Yes
<b>Italian</b>	Yes
<b>Russian</b>	Yes
<b>Spanish (Latin America)</b>	Yes
<b>Thai</b>	Yes
<b>Turkish</b>	Yes
<b>Vietnamese</b>	Yes
<b>Ruijie Cloud management</b>	Yes
<b>Scheduled device restart</b>	Yes
<b>eWeb login password length</b>	8 to 63 characters
<b>Wired repeater mode</b>	Yes
<b>Wireless repeater mode</b>	Yes
<b>WISP mode</b>	Yes
<b>Rate Limiting</b>	
<b>Client-based rate limiting</b>	Yes
<b>Reyee Mesh 3.0</b>	
<b>Reyee Mesh 3.0</b>	Yes
<b>Automatic switching between wired and wireless repeater mode</b>	Yes

# Software Specifications

Model	RG-EW7200BE PRO
<b>Recommended hop count</b>	2
<b>Maximum number of clients</b>	192
<b>Maximum number of devices</b>	32
<b>Security</b>	
<b>Encryption mode</b>	Yes
<b>System Performance Capacity</b>	
<b>Maximum number of concurrent clients</b>	128 (2.4 GHz) 256 (5 GHz)
<b>Recommended number of concurrent clients</b>	16 (2.4 GHz) 64 (5 GHz)
<b>IPTV/IGMP client capacity</b>	5
<b>IPTV/IGMP multicast capacity</b>	5
<b>IPTV/IGMP wired forwarding performance</b>	25 Mbps
<b>Recommended camera limit</b>	6 (2.4 GHz) 16 (5 GHz)
<b>VPN</b>	
<b>Number of concurrent tunnels supported by the OpenVPN server</b>	8
<b>Certificate authentication</b>	Yes
<b>OpenVPN bandwidth</b>	13 Mbps
<b>OpenVPN client</b>	Yes
<b>OpenVPN server</b>	Yes
<b>Server domain name configuration</b>	Yes
<b>Username and password authentication</b>	Yes
<b>Number of concurrent tunnels supported by the PPTP VPN server</b>	30
<b>PPTP VPN client</b>	Yes

## Software Specifications

Model	RG-EW7200BE PRO
PPTP VPN server	Yes
<b>Wireless Configuration</b>	
Guest Wi-Fi	Yes
<b>WLAN</b>	
1024-QAM	Yes
MLO	Yes
DFS	Yes
802.11k/v roaming	Yes
Wi-Fi blocklist capacity	64
SSID hiding	Yes

## Package Contents

Model	RG-EW7200BE PRO
<b>Accessories</b>	
Ethernet cable	1
Power adapter	1
<b>Device</b>	
Device	1
<b>Manual</b>	
User Manual	1
Warranty Card	1

**Ruijie** | Reyee

 **Redefine your easy network**



**Ruijie Networks Co., Ltd.**  
Official Website: <https://Reyee.Ruijie.com>