



**TITLE:**

ISP Individual Foil Screen LSZH

**CODE:**

SFX/ISP2-LSZH-D-GRY-100

**DESCRIPTION:**

100m ISP2 2pr 22AWG Individual Foil  
Screen 600V Grey LSZH (8723)

**SUPPLIED AS:**

Reel of 100m



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**



**IMAGE  
COMING  
SOON**





## Product Specification

### Cable Construction

Cable Construction	2 Pairs
CPR	Dca -s:2 -a:1 -d:2
Conductor	Tinned Copper
Conductor Diameter (mm)	0.24 ±0.008 x 7 (0.33mm <sup>2</sup> )
Overall Diameter (mm)	4.10 ±0.20

### Insulation

Insulation	PE
Insulation Colour	Red,Black;Green,White
Insulation Resistance @20°C	>200MO/km
Insulation Thickness (mm)	0.24

### Outer/Jacket Specification

Jacket	LSZH
Overall Colour	Grey
Overall Diameter (mm)	4.10 ±0.20
Jacket Colour	Grey RAL 7042
Jacket Thickness (mm)	0.45
Nylon Rip-Cord	White 210D

### Electrical Characteristics

Insulation Resistance @20°C	>200MO/km
Max Conductor DC resistance @ 20°C	<50O/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V





**BELDEN  
EQUIVALENTS**



## **MORE INFORMATION:**

**Sorry, no more information is available for this product**

**Belden equivalents**



**enquiries@securiflex.co.uk | www.securiflex.co.uk | 03333 44 66 23**

TERMS AND CONDITIONS APPLY - WHILE EVERY EFFORT HAS BEEN MADE TO ENSURE THE ACCURACY AND COMPLETENESS OF THE INFORMATION, NO GUARANTEE IS GIVEN NOR RESPONSIBILITY TAKEN FOR ERRORS OR OMISSIONS IN THIS DATA SHEET.

